

# 16Slots 4U RACK



Model: AZ-CH04



## Description:

The 4U/16port rack(AZ-CH04) can support for 16 interface converter card. every card could work independently and different types of interface converter card can be inserted in one rack ; the system power supply is separated from interface converter by communication insulation technology, so that the reliability of the system can be ensured.

## Feature:

- Can insert various types of interface converter produced by our company
- 19-Inch 4U standard rack, using the principle of air, good rack radiating performance, ease of management and maintenance
- Can insert up to 16 hot-plug cards, each interface conversion card can achieve conversion function independently
- Two power panel slots support mutual hot spare between two power units. Each power unit can support the entire rack work full of configuration. Two power units work together through shunt on the one hand to reduce each power unit load, on the other hand by mutual hot spare to ensure if one power unit having problem within the time rack inner function panel can work
- Support SNMP Network Management
- Fully meet Telecom operation requirements, Mean time Between Failures (MTBF) is more than 50,000 hours.



**Work condition:**

operating temperature: 0 °C ~70 °C  
storage temperature: -40 °C ~85 °C  
relative temperature: 5%~95% non-condensing

**power supply card:**

option I – DC48V,range DC36V~DC72C  
option II – AC220V,range AC90V~AC240V

**Dimension:**

480mm(L)  
270mm(W)  
175mm(H)

**Order information:**

AZ-CH04 4U rack mount chassis,17slots for E1 converters,fiber modem, fiber multiplexer,two power supply,SNMP management