

Unmanaged Chassis Media Converter

Model:AZ01



Product function:

Transmit 10/100Base-T Ethernet electrical signal through fiber, realize TX/FX converter. AZ01 is a kind of cost-effective media converter rack (2U) widely used in the equipment room. Different types of modular media converter or standalone media converters can be inserted into this rack, which total slots up to 14. It is furnished with two power supplies: main power supply and spare one, and supports its automatic switch-over.

Features:

1. The configuration of active/standby power supply ensures uninterruptible operation of the system.
2. Provide two power supplies (AC 220V, and DC -48V), enabling the system can work under many operating environments;
3. Supporting simultaneous operation of several module type (module type) media converters at different rates, which greatly improves system adaptability;
4. Each card supports hot swapping;
5. Applicatory module types: AZ-100M series, AZ-1000M series.

Parameter:

Parameter	Specifications
Number of slots	14
Structure	2U rack
Power input	AC Voltage: AC 85~265V; frequency: 50/60 Hz
	DC voltage: DC -36~72V
Power output	DC5V 16A
Power configuration	Single power supply, or dual power supply for warm backup mode
LED indication	POWER (power supply)
Max power consumption	95W

Azmoon Keyfiat CO.

Website: www.azmoon-co.com

Email: azmoon@teta.net

Tell: +9821-84218



Operating temperature	-10~55iC
Operating humidity	5%~90%
Maintaining temperature	-40~70iC
Maintaining humidity	5% ~ 90% non-condensing
Dimensions of rack	90mm (H) * 485mm (W) * 245mm (D)

Order information:

AZ01/AC+AC	AZ01 chassis with two AC power
AZ01/DC+DC	AZ01 chassis with two DC power
AZ01/AC+DC	AZ01 chassis with AC+DC power
AZ01/AC	AZ01 chassis with AC power
AZ01/DC	AZ01 chassis with DC power